
TP50

PRINTER



ETHERNET



USB



RS232

THERMAL PRINTER


Ethernet

USB

RS232

Multi OS compatible

CONFIGURATIONS



TP50

Print method	Thermal
Effective print width	80mm or 58mm
Paper loading	automatic
Emulation	Epson / Star / Esc / Pos

SETTINGS

Printing	Monochrome or bi colour (special paper)
Print speed	250mm/s 59 lines/s
Thermal printer paper	80mm 79,50 ± 0,50 (L)mm x dia 83,00 mm ou 58mm 57,50 ± 0,50 (L)mm x dia 83,00mm
Print width	72mm - 48mm/54mm
Characters per line	42/21 Fonte A - 56/28 Fonte B 180DPI
Font	95 Alphanumeric, 37 International, 128*11 Graphic, Korean
Barecodes	UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF, CODABAR, PDF417, QR Code
Cut type	Total or partial
Sensor	End-of-roll, cover open
Interfaces	USB type B, RS-232 type RJ45 network RJ45, cash drawer RJ11 24V 2 drawers opening compatible
PGM and graphic logo	Yes 2Mbyte + 8Mbyte
Internal memory	64MB
OS	Windows XP / Vista(*86)/ 7/ 8, 2003 Server Driver, OPOS Driver, Linux, Android

VARIOUS

Dimensions H x W x D	131 x 155 x 133mm
Weight	0.9Kg
Colours	Black or White lacquered
Power supply	100~240AC (50~60Hz) 24VDC 2,5A
Settings	Horizontal, Vertical (Option sup mural)
Cables & Power supply	Mains supply, RS232 cable, USB cable
Options	Wall mount, Buzzer 58mm print reducer
Certifications	CE FCC, class A, TUV/GS, CE, CB, cTUVus
Operating temperature	5°C ~ 45°C
Storage temperature	-10°C ~ 50°C
Operating humidity	5% ~ 90% (without paper)
Option	Kitchen alarm

MODELS

Auto cutter	1,500,000 Cut
Printer head lifespan	150Km
Number of lines	70,000,000

TP50

TP50 WIFI



Specifications are subject to change without notice. © OXHOO 2019

