

---

# BC412

---



1D IMAGER READER  
SMARTPHONE COMPATIBLE

---



BC412W



White

## BC412

Barecode reader	1D imager
<b>Smartphone compatible</b>	
<b>CPU</b>	<b>32Bit ARM</b>
Operating mode	Gun or automatic
Light source	CCD 625nm
Résolution de l'image	2500 pixels
Source de lumière	LED, 625nm~10nm
Précision	sup ou = 5mm
Reading confirmation	Buzzer + LED

## CONNECTIONS

USB	1
-----	---

## SETTING

Activation	Manual or automatic
Trigger	yes
Reading size	30mm; 200x200mm
Reading distance	40-300mm
Interface	USB
1D bar type	EAN8, EAN13, UPC-A, UPC-E, Code39, Code128, EAN128, Codabar, Ind. 2of5, ISBN/ISSN, Code 93, GS1

## VARIOUS

Dimensions l x L x H	170mm x 68mm x 98mm
Weight	150gr
PC cable	2M
Reader colour	white
Voltage	5V
Power consu. max	70mA
Certifications	CE(EMC) Class B, Rohs
Operating temp.	-20°C – 60°C
Storage temp.	-40°C – 85°C
Humidity	5% - 95% (Sans condensation)



Specifications are subject to change without notice. © OXHOO 2019

