

---

# EVOOQ

INFINITELY INNOVATIVE

---



4:3  
SCREEN

  
CAPACITIVE  
MULTI-TOUCH



  
MICROSOFT

  
FANLESS

  
SSD  
M.2

  
NVMe  
M.2

# CONFIGURATIONS



## EVOQ

Cooling	FANLESS
Frame	Aluminium
Screen	15.1" True Flat 4/3 LED
Resolution	1024 x 768
Touch panel	Multi-Touch (PCAP)
Memory RAM	1 x DDR4 4GB 2133MHz SO-DIMM (1 Slot 16 GB Max)
Storage	1 x M.2 SSD 128 GB

## MODEL

### EV395K

Processor	Intel Kaby Lake Celeron 3965U
Graphic controller	Intel HD Graphic DX12
Graphic memory	Partagée
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

### EV645E

Processor	Intel Elkhart Lake 6412
Graphic controller	Intel HD Graphic 12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

### EV455K

Processor	Intel Tiger Lake i3-1115G4
Graphic controller	Intel HD Graphic 12.1
Graphic memory	Shared
Network controller	Realtek PCIe GBE
Audio controller	Realtek ALC662-HD Audio

## OS COMPATIBLES

Windows 11

Windows 10 (64 bits)

## INPUT/OUTPUT

Network	1 x RJ45
Connectors	2 x M.2 SSD ou NVMe (M-key)
USB Type A	2 x USB 3.0
	3 x USB 2.0 (1 in front)
USB Type C	2
FeDP	2
Serial COM RS232	2 (COM1 & COM2 DB9-COM+5V/+12V)
Cash drawer	1 x 12V/24V
DC-IN	1 x 4 pin w/lock
Power supply	90W/19V

## VARIOUS

Dimensions l x L x H	328 x 262 x 339 mm
Weight	4.5kg
Colours	Black
Setup	Horizontal from 0° to 90°
Certifications	FCC/CE Class A, LVD
Operating temperature	0°C ~ 35°C
Storage temperature	-10°C ~ 50°C
Humidity	20% ~ 85% without condensation

## PACKAGING

Unit	1
Dimensions l x L x H	478 x 323 x 495mm
Weight	6.5kg

## OPTIONS

Integrated customer display
2 <sup>nd</sup> capacitive screen 11.6"
2 <sup>nd</sup> screen 11.6"
2D scanner reader
ISO 1/2/3 (MSR) barcode
Fingerprint reader
Hub USB retail 1 x 24V 2 x 12V



Specifications are subject to change without notice. © OXHOO 2022

