

RETAIL BOX





RB356S

RETAIL BOX

Processeur	Intel Skylake S CPU i3 6100TE
Chipset	Q170 / H110
Mémoire	2x DDR4 2133MHz SO-DIMM (max. 32GB) (dual channel)
Stockage	2x 2.5" SATA SSD
Mémoire graphique	Intel HD Graphics Compatible AMT/vPro

EN FAÇADE

USB	1x USB 3.0 1x USB Type C
Bouton power	1
Indicateur LED	1
Indicateur LED HDD	1

ENTRÉES / SORTIES

USB	2x USB 3.0 2x USB 2.0
USB Retail	2x USB/Retail 12V 1x USB/Retail 24V
Ports séries	3x DB9 (COM1/2 powered RS232, COM3 powered RS232/422/485) (default 0V; 0V/5V/12V enabled by BIOS setting)
LAN	1x RJ45
Tiroir-caisse	1x RJ11 (default 24V, 12V/24V)
VGA	1x DB15 (default 0V, 0V/12V)
Display Port	2
Audio Line-out	1
Audio Mic-in	1

OPTION

PCI-E Slot	2x Riser Card (1x PCI-E x1 slot & 1x PCI-E x16 slot)
COM4/ COM5/ DC-12V out	1 (2 x DB9, 1x 12V Power Output)
Powered USB Module	5x USB/Retail 12V
Port parallèle	1
PS/2	1

OS COMPATIBLES

AMT/vPro et RAID compatible
Windows 10 (64bit), Windows 10 IoT Enterprise (64bit), Windows 7 (64bit), POS-Ready 7 (64bit), Linux

DIVERS

Alimentation	Interne ATX 250W
EMC & Sécurité	FCC Class B, CE Mark, LVD
Température de fonctionnement	5°C ~ 35°C (41°F ~ 95°F)
Température de stockage	-20°C ~ 55°C (-4°F ~ 131°F)
Humidité	20% ~ 85% RH sans condensation
258 x 300 x 132 mm	
6,5 kg	

