oxhoo
INFINIMENT POINT DE VENTE

BINGO

300dpi
Resolution

104mm
Printing Width

14 ips
Printing Speed



LABELS

CONFIGURATIONS

BINGO

Printing method	Direct thermal
	Thermal Transfer
Resolution	203 dpi /300 dpi / 600 dpi
Max.Printing Speed	14 ips (203 dpi) / 8 ips (300 dpi) / 4 ips (600 dpi)
Max.Printing Width	104mm
Max.Pringting Length	2 286 mm (203 dpi) / 1 524 mm (300 dpi) / 762 mm (600 dpi)
Programming Language	ZPL, DPL, EPL, TSPL

DETECTION

Sensor	Continuous Paper, Gap, Black Mark,
	Punched Hole Label
Detection	Print Frame Open Detect
	Ribbon End Detect
	Paper Out Detect
	TPH Over Heating Detect

MEDIA

Type	Continuous Paper, Gap, Black Mark,
	Punched Hole Label
Width	25 mm ~ 120 mm
Thickness	80 µm ~ 250 µm
Label Roll Diameter	25.4 mm
Core Diameter	1.5''(38 mm) ~ 3''(70mm)

RIBBON

Type	Wax, Wax/Resin, Resin
Width	30 mm ~ 110 mm
Length	450 m

INTERFACES

	USB Type B,Ethernet, Serial

BARCODE

1D	UPC-A, UPC-E, EAN128, Codabar, CODE128, CODE39, CODE93, EAN-8, EAN-13, UCC/EAN128,POSTNET,ITF14,HIBC,MSI,Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13, Japanese Postnet, Interleaved 2 of 5, Standard 2 of 5, Industrial 2 of 5, Logmars, CODE11
2D	CODE49, CODABLOCK, PDF417, Data Matrix, Maxicode, QR Code, MicroPDF471, Aztec

MEMORY

RAM	512 MB
Flash	256 MB

DIMENSIONS

Dimensions l x L x H	460.4*263.6*330.5 mm
Weight	12.5 kg

VARIOUS

Colour	Black
Power	100~240AC (50~60Hz) 24VDC 2,5A
Cable & power supply	Power supply, USB cable
Certifications	CE FCC, class A,TUV/GS, CE, CB, cTUVus
LCD	4 indicators
	6 buttons









Non-contractual document, subject to change without notice. OXHOO © 2022

OXHOO UK Ltd
14 Seymourt Court, Runcorn, Cheshire WA7 1UZ
Phone : (+44) 01928 579 824
contact@oxhoo.com - www.oxhoo.com