oxhoo
INFINIMENT POINT DE VENTE

TLP 200

300dpi
Resolution

118mm
Printing Width

4/5 ips
Printing Speed



LABELS

CONFIGURATIONS

TLP200

Printing method	Direct thermal
	Thermal Transfer
Resolution	203 dpi / 300 dpi
Max.Printing Speed	5 ips(203 dpi) / 4 ips(300 dpi)
Max.Printing Width	108 mm(203 dpi) / 106 mm(300 dpi)
Max.Pringting Length	2 286 mm(203 dpi) / 1 524 mm(300 dpi)
Programming Language	ZPL-II, EPL-II, TSPL

DETECTION

Sensor	Continuous Paper, Gap, Black Mark,
	Punched Hole Label
Detection	Print Frame Open Detect
	Ribbon End Detect
	Paper Out Detect
	TPH Over Heating Detect

MEDIA

Type	Continuous Paper, Gap, Black Mark,
	Punched Hole Label
Width	1''(25.4 mm) ~ 4'' (118 mm with support)
Thickness	60 µm ~ 250 µm
Label Roll Diameter	127 mm
Core Diameter	0.5''(12.7 mm), 1''(25.4 mm). 1.5''(38 mm)

RIBBON

Type	Wax, Wax/Resin, Resin
Width	30 mm ~ 110 mm
Length	100 m
Core Diameter	12.7 mm

INTERFACES

	USB Type B, Ethernet

DRIVERS

	Bartender Ultralite
	Windows 7,8,10, Server 2008,2012
	CUPS for Linux and MAC OS

BARCODE

1D	UPC-A, UPC-E, EAN128, Codabar, CODE128, CODE39, CODE93, EAN-8, EAN-13, UCC/EAN128,POSTNET,ITF14,HIBC,MSI,Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13, Japanese Postnet, Interleaved 2 of 5, Standard 2 of 5, Industrial 2 of 5, Logmars, CODE11
2D	CODE49, CODABLOCK, PDF417, Data Matrix, Maxicode, QR Code, MicroPDF471, Aztec

MEMORY

RAM	128 MB
Flash	256 MB

DIMENSIONS

Dimensions l x L x H	252*201*181 mm
Weight	1.8 kg

VARIOUS

Colour	Black
Power	100~240AC (50~60Hz) 24VDC 2,5A
Cable & power supply	Power supply, USB cable
Certifications	CE FCC, class A,TUV/GS, CE, CB, cTUVus
Operation	5°C ~ 50°C
Operation Humidity	25% ~ 85% (without condensation)
Storage	-40°C ~ 60°C
Storage Humidity	10% ~ 90% (without condensation)

OPTIONS

Bluetooth

Wi-Fi

Non-contractual document, subject to change without notice. OXHOO © 2022









OXHOO UK Ltd
14 Seymourt Court, Runcorn, Cheshire WA7 1UZ
Phone : (+44) 01928 579 824
contact@oxhoo.com - www.oxhoo.com